Specifications. The BMW Series 5 Sedan. M550i xDrive.



		BMW M550i xDrive Sedan
Dadu		
Body No of doors (contact)		4/5
No of doors/seats		
Length/width/height (unladen)	mm	4962/1868/1467
Wheelbase	mm	2975
Track, front/rear	mm	1600/1597
Ground clearance	mm	131
Turning circle	m	12,24
Fuel tank capacity	Approx. Itr	68
Engine oil ¹⁾	ltr	10,0
Weight, unladen, to DIN/EU	kg	1810/1885
Max load to DIN	kg	650
Max permissible weight	kg	2460
Max axle load, front/rear	kg	1230/1300
Max trailer load,	kg	2000/750
Braked (12%)/unbraked	J	
Max roofload/max towbar download	kg	100/90
Luggage comp capacity	ltr	530
Air resistance	C _d x A	0,28 x 2,35
7 III TOOIGEATIOC	O ₀ X Y Y	0,20 x 2,00
Power Unit		
Config/No of cyls/valves		V/8/4
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, direct injection system High Precision Injection, fully variable valve control VALVETRONIC, variable camshaft timing Double VANOS
Effective capacity	CC	4.395
Stroke/bore	mm	88,3/89,0
Compression ratio	:1	10,5
Fuel		min. RON 91
Max output	kW/hp	340/462
at	rpm	5500–6000
Max torque	Nm/lb-ft	650/479
at	rpm	1800–4750
<u></u>		
Electrical System		
Battery / installation	Ah/–	105/ Luggage
Alternator	A/W	compartment n.b.
Driving Dynamics and Safe Suspension, front	ty	Aluminium double track control arm axle with separate lower track arm level,
Suspension, Ironic		small positive steering roll radius, traverse force compensation, anti-dive
Sucnoncion roor		Five-link axle in aluminium lightweight construction
Suspension, rear		
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), Networked with xDrive all-wheel-drive system in Integrated Chassis Management, DBC (Dynamic Brake Control), Dry Braking function,
		Fading Compensation, Start-Off Assistant. Optional: Dynamic Damper Control, Drive Performance Control
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, tyre defect indicator
Steering		Electric Power Steering (EPS)
Steering ratio overall	.1	optional: Integral Active Steering
Steering ratio, overall Tyres, front/rear	:1	16,3 245/40 R19 98Y/
		275/35 R19 100Y
Rims, front/rear		8,0J x 19 light alloy/

			BMW M550i xDrive Sedan
Transmission			
Type of transmiss	nion		8-speed Steptronic
Gear ratios	I I	:1	5,000
Geal Tallos	<u>'</u>	:1	3,200
	<u>"</u> 	:1	2,143
	IV	:1	1,720
	V	:1	1,313
	VI	:1	,
			1,000
	VII VII	:1	0,823
		:1	0,640
	R	:1	3,478
Final drive		:1	2,813
Performance			
Power-to-weight	ratio	kg/kW	5,3
Output per litre		kW/ltr	77,4
0–100 km/h		sec	4,0
In 5th gear	80-120 km/h	sec	
Top speed		km/h	250
BMW Efficient	Ovnamics		
BMW EfficientDy			Brake Energy Regeneration, electromechanical power steering, Automatic
standard features		С	tart/Stop function, ECO PRO mode with coasting function, intelligent lightweight onstruction, optimised aerodynamic attributes, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised-warm-up behaviour, tyres with reduced rolling resistance
	2)		tyres with reduced rolling resistance
Fuel Consumpt	tion ECE ²⁾		
Urban		ltr/100 km	12,7
Extra-urban		ltr/100 km	6,8
Combined		ltr/100 km	8,9
CO ₂		g/km	204
Emission rating			EU6

Preliminary Specifications apply to ACEA markets/data relevant to homologation apply in part only to Germany (weight)

 $^{^{1)}}$ Oil change $^{2)}$ Fuel consumption and CO_2 emissions depend on the selected tyre format

BMW Mediainformation Page 3

Output and torque diagrams. The BMW Series 5 Sedan.





