## Technical specifications. BMW M8 Convertible.

## BMW M8 Convertible. M8 Competition.



01/2021 Page 1

	BMW M8 Competition Convertible				
Body					
No of doors/seats		2/4			
Length/width/height (unladen		4867 / 1907 / 1353			
Wheelbase	mm	2827			
Track, front/rear mm		1623 / 1632			
Ground clearance	mm	114			
Turning circle	m	12.2			
	pprox. l	68			
Engine oil 1)		10.0			
Weight, unladen, to DIN/EU	kg	2025 / 2100			
Max load to DIN	kg	415			
Max permissible weight	kg	2440			
Max axle load, front/rear	kg	1215 / 1260			
Max trailer load,					
braked (12%)/unbraked	kg	-/-			
Max roofload/max towbar					
download	kg	-/-			
Luggage comp capacity	Ī	350			
Air resistance	c <sub>d</sub> x A	0.33 x 2.25			
Power Unit					
Config/No of cyls/valves		V/8/4			
Engine technology		M TwinPower Turbo technology with cross-bank exhaust manifold: M			
Lingine technology		TwinScroll twin turbocharger, indirect charge air cooling, High Precision			
		Injection (maximum injection pressure: 350 bar), VALVETRONIC fully			
		variable valve timing, Double-VANOS variable camshaft timing			
Effective capacity	СС	4395			
		88.3 / 89.0			
Stroke/bore	mm				
Compression ratio	:1	10.0			
Fuel	11-14	RON 98 (min. RON 91)			
Max output	kW/hp	460 / 625			
at	rpm	6000			
Max torque	Nm	750			
at	rpm	1800 – 5860			
Electrical System					
Battery/installation	Ah/-	70 / luggage compartment			
Duising Dynamics and Safaha					
Driving Dynamics and Safety Suspension, front		Adaptive M suspension with double wishbone axle in lightweight aluminium			
Suspension, none	,	construction, M-specific kinematics and elastokinematics			
Suspension, rear		Adaptive M suspension with five-link axle in lightweight aluminium			
Suspension, reur		construction, M-specific elastokinematics			
Brokes front					
Brakes, front		M compound brakes, vented, with six-piston fixed callipers  M compound brakes, vented, with single-piston floating callipers			
Brakes, rear					
Driving stability systems		Standard: DSC incl. ABS, ASC and M Dynamic Mode (MDM), can be			
	switched off, CBC (Cornering Brake Control), DBC (Dynamic Brake Control),				
	Dry Braking function, Start-Off Assistant, Active M Differential, DSC linked				
		with M xDrive all-wheel drive			
Safety equipment	Standard: airbags for driver and front passenger, side airbags for driver and				
	front passenger, head airbags for front and rear seats, three-point inertia-				
		reel seatbelts on all seats with belt stopper, belt latch tensioner and belt			
		force limiter in the front, crash sensors, rollover protection system,			
<del></del>		tyre pressure indicator			
Steering		Electric Power Steering (EPS) with M-specific Servotronic function			
		and variable sport ratio			
Steering ratio, overall	:1	14.3			
Tyres, front/rear		275/35 ZR20 102Y XL			
		285/35 ZR20 104Y XL			
Rims, front/rear		9.5J x 20 light-alloy			
		10.5J x 20 light-alloy			

## **BMW M8 Competition Convertible**

## Power transfer

M xDrive intelligent all-wheel drive, central transfer case with fully-variable multiplate clutch, fully-variable torque distribution between front and rear axle, rear differential with fully-variable Active M Differential, locking effect 0 – 100 per cent

Transmission					
Type of transmission			Eight-speed M Steptronic transmission with Drivelogic,		
			transmission oil cooling		
Gear ratios	I	:1	5.000		
	II	:1	3.200		
	III	:1	2.143		
	IV	:1	1.720		
	V	:1	1.313		
	VI	:1	1.000		
	VII	:1	0.823		
	VIII	:1	0.640		
	R	:1	3.478		
Final drive		:1	3.154		
Performance					
Power-to-weight ratio (DIN)		kg/kW	W 4.4		
Output per litre		kW/l	104.7		
Acceleration	0–100 km/h	S	3.3		
Acceleration	0-200 km/h	S	11.3		
Top speed		km/h	250 / 305 <sup>2)</sup>		
BMW Efficient	Dynamics				
BMW EfficientDynamics			Brake Energy Regeneration, Electric Power Steering, Auto Start Stop		
standard features		function, Optimum Shift Indicator in manual shift mode, BMW			
			EfficientLightweight, on-demand operation of ancillary units, Li-ion		
			battery, map-regulated oil pump, rear differential and transfer case with		
			optimised efficiency, optimised aerodynamics (underside panelling, from		
			spoiler, rear spoiler)		

Fuel Consumption ECE			
Urban (NEDC)	I/100 km	16.9 – 16.8	
Extra-urban (NEDC)	I/100 km	8.2 – 7.9	
Combined (NEDC)	I/100 km	11.4 – 11.2	
Combined (WLTP)	I/100 km	11.6 – 11.2	
CO <sub>2</sub> (NEDC)	g/km	262 – 257	
CO <sub>2</sub> (WLTP)	g/km	264 – 255	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

Official fuel consumption,  $CO_2$  emissions, electric power consumption and electric range figures were determined based on the prescribed measurement procedure in accordance with European Regulation (EC) 2007/715 in the version applicable. They refer to vehicles in the German market. Where a range is shown, NEDC figures consider the different sizes of the selected wheels/tyres, while WLTP figures take into account the impact of any optional extras.

WLTP values are used for determining vehicle-related taxes or other duties based (at least inter alia) on  $CO_2$  emissions as well as eligibility for any applicable vehicle-specific subsidies. Any NEDC values that are shown were calculated based on the new WLTP measurement procedure where appropriate and translated back into equivalent NEDC measurements in order to ensure comparability between the vehicles. Only official figures based on the WLTP procedure are available for new models that have been type tested since 01.01.2021. Further information on the WLTP and NEDC measurement procedures can also be found at www.bmw.com/wltp.

 $<sup>^{1)}</sup>$  Oil change with filter

<sup>2)</sup> Limited / with optional M Driver's Package